

EURO 3310



Piezo switch engineering, safe, water-tight and indestructible



Free access to the rear blade surface and beveling makes the blade protection ring easy to clean



Hard-chromium plated special high-performance blade Ø 330 mm



Generously sized, smooth-running carriage with 300 mm slicing length

EURO 3310 in standard version

The EURO 3310 provides great ease of use, ergonomic handling and exemplary cleaning facilities for professional use.

BENEFITS

- Special high-performance blade Ø 330 mm hard-chromium plated
- Internal blade cover plate
- High-torque, smooth-running motor, double ball-bearing support with 500 watts for ideal traction even with difficult slicing items
- Air cooling system to prevent the housing and blade from heat build-up
- Piezo switch engineering
- Generously sized, smooth-running carriage with ball-bearing supported interior carriage (slice length 300 mm), can be removed for cleaning
- Precisely machined guide grooves in limit and blade cover plate for superior gliding attributes
- Closed base plate
- Slice product support
- Slicing thickness setting 0 – 24 mm
-
-



TECHNICAL DATA

Product no.	EURO 3310	
Motor power	500 watts	230 V~ alternating or 400 V~ three-phase current
Blade (Ø mm)	Ø 330 mm, smooth, solid steel blade	
Blade speed	230/rpm	
Slice thickness max.	24 mm	
Emission noise level	< 69 dBA	
Slice size (L x H mm)	300 x 223 mm	
Slice dimension (L x W mm)	300 x 340 mm	
Footprint (L x W mm)	540 x 440 mm	
Exterior dimensions (L x W x H)	650 x 605 x 445 mm	
Workspace (L x W x H)	740 x 725 x 600 mm	
Net weight	37.9 kg	
Operating period	Continuous duty	
Warranty	2 years	

ACCESSORIES

- Special oil
- 2-disc blade sharpener

OPTION



Blade in non-stick version

